

Wellbeing 450mm Straight Grab Rail

EC450

Fully welded construction in grade 304 stainless steel tubing. Slip resistant Stainless Steel with flange covers. Standard 32mm diameter. Easy to install on most building surfaces (fixings not supplied). Designed for maximum strength and user confidence.

Available in lengths from 300mm to 1100mm centre of flange to centre of flange. Conforms to AS1428.1-2009.

FEATURES

- CleanSeal flange and cover with a simple fixing method and a hygienically mounted installation.
- Provides for easily cleaned crevice-free condition that inhibits bacterial build up.

Product Codes

EC450SS	Stainless Steel Finish
EC450CP	Chrome Plated (Bright 3 Stainless Steel Finish)
EC450WH	White Powdercoat Finish
EC450BLK	Black Powdercoat Finish

OPTIONS

- Chrome plated (Bright 3 stainless steel) or powder coated finish (Black or White)
- Anti-Ligature - Stainless Steel Finish - **EC450ALIGSS**



Load Rating:

Enware Grab Rails that are manufactured within the guidelines of AS1428 are compliant with being able to withstand 1100N of force applied in any direction.

Fixing screws are not supplied with product. Ensure grab rail is installed on a solid wall surface with firm wall backing using appropriate fixing method. Structural engineers or licensed tradespersons should be consulted for appropriate advice on suitability of the fasteners and wall structure before affixing or installing any Enware products. Enware does not provide any warranty in relation to bolts, screws or other fasteners used with Enware products.

NOTE: Enware Australia advises:

1. Due to ongoing Research and Development, specifications may change without notice.
2. Component specifications may change on some export models.
3. Refer to Warranty Statement for warranty details - www.enware.com.au/warranty



Version: May 21

Call 1300 369 273
www.enware.com.au

Enware Australia Pty Limited
9 Endeavour Rd Caringbah NSW 2229 Australia
Ph: 02 8536 4000 info@enware.com.au

