

# Single Button Control Kit: Front Access for In Wall Application

The water efficient Detention tapware series have been designed to provide a high level of security with the inclusion of vandal resistant features.

## KEY FEATURES

- Stainless steel face plate, in wall mounting bracket and secure screws
- Touch-activated Piezo button with 1/2" Stainless Steel solenoid valve
- 24V DC power pack and 4.5m cable requires 240V GPO
- Factory set run time, adjustable on site
- Factory set run time - 4 minutes with early stop enabled and 30 seconds time out
- Adjustable from 3 seconds up to 10 minutes run time, with lockout and touch off function
- Ideal for Detention, public areas, council and camping facilities.
- For Shower or Basin controls
- Suitable for Cold or Pre-mixed (warm water)
- IP68 Rated Piezo button



## PRODUCT CODES

EMD811SS	Single Button Control Kit: Front Access for In Wall Application - Programmable Timing
----------	---

Due to ongoing Research and Development, specifications may change without notice.

Component specifications may change on some export models.

Refer to warranty statement for warranty details - [www.enware.com.au/warranty](http://www.enware.com.au/warranty).

Products are to be installed in accordance with the Plumbing Code of Australia and AS/NZS3500.

Reference should also be made to the Australasian Health Facility Guidelines (AHFG), ABCB and Local Government regulations when considering the choice of, and the installation of these products.



# Single Button Control Kit: Front Access for In Wall Application

## SPARE PARTS

EMDS802	Spare Parts: Transformer Piezo 24VDC 1.25A 4.6m Lead
EMS811	Spare Parts: Touch Button - Electronic Programmable Button
EMS816	Spare Parts: 1/2 SOLENOID VALVE DC S/S 24VDC
WMS8302	Spare Parts: 1/2" DC SOLENOID SEAL KIT
EMDS801-4.5	Spare Parts: 4.5 Metre Extension Cable