# School Pattern Recessed Set With SP263 Shower


Enware's vandal resistant School Pattern tapware is constructed from dezincification resistant (DR) brass with durable chrome plating and an easy to clean design. The handle features a vandal resistant internal locking ring securing it to the spindle and requires a special key to remove. For areas where there is a higher risk of vandalism choose the School Pattern non-removable handle (VPN), which utilises a handle permanently fixed to the spindle.

**VP349** 

MAX HEIGHT 255

#### Features:

- High quality construction
- Supplied complete with handles, buttons and shower outlets
- Comprehensive 12-month warranty
- Serviceable with all wearing components replaceable, thus providing a longer life
- WELS 3 Star (7.7 lpm) water efficiency rating supplied as standard



#### **Product Codes**

VP349 Jumper Valve

**VP349S** Jumper Valve (School Specification - SP264)

**VPH349** 1/2 Turn Ceramic Disc **VPQ349** 1/4 Turn Ceramic Disc **VPT349** 3/4 Turn Ceramic Disc

## **Technical Information**

Working Pressure Range Ceramic Disc	50-800kPa
	500kPa Max (PCA)*
Working Pressure Range Jumper Valve	30-1200kPa
	500kPa Max (PCA)*
Maximum Working Temperature*	Ceramic Disc - 85°C
	Jumper Valve - 95°C

\*Enware products are to be installed in accordance with AS/NZS3500.

Heated Water Supply AS/NZS 3500.4: For all sanitary fixutres used primarily for personal hygiene purposes are to deliver heated water not exceeding:

a) 45°C for early childhood centres, primary and secondary schools and nursing homes or similar facilities for young, aged care, sick people with disabilities (43.5°C - NSW Code of Plumbing Practice)

b) 50°C in all other buildings

### NOTE: Enware Australia advises

Due to ongoing Research and Development, specifications may change without notice.

2. Component specifications may change on some export models

# Wall Depth Adjustments:

Enware's Recess taps have adjustments for installation flexibility - Spindle Extensions are available in 15, 20, 25, 30 and 40 mm.








Version: MAR13

# Call 1300 369 273 www.enware.com

Enware Australia Pty Limited 9 Endeavour Rd Caringbah NSW 2229 Australia Ph: +61 2 8556 4000 Fax: +61 2 8556 4055





205 (MIN)

370 (MAX)